

JUMBO™ RAMP BOLT FIXINGS - ASPHALT

PRODUCT CODE: HAJ000-000-000

FIXING BOLTS FOR USE WITH JUMBO™ RAMP ON ASPHALT SURFACES

**TECHNICAL
SPECIFICATION**

TRAFFIC MANAGEMENT

INSTRUCTIONS FOR USE

Position the units at the end of a row and mark the location of the fixing holes on the surface to be applied to

Remove speed bumps and drill holes at the marked positions as follows: Asphalt – 24mm Diameter Hole Size, Minimum Depth 85mm. The correct fixing for the surface must be used.

Clean hole of debris

Insert bolt shield into hole

Reposition units and pass the bolts through the locating holes and screw into the shield

Tighten bolt to a torque of: 15-20NM

It is responsibility of the Landowner/Leaseholder to place appropriate signage to indicate the speed limit at which the Speed Bumps should be approached



Materials:

Zinc Plated Steel Bolt
& Zinc Plated Shield
C/W Rubber Collar



JUMBO™ RAMP ASPHALT BOLT FIXING FEATURES

Pre-Drilled Bolt Holes: All sections are pre-drilled ready for inserting relevant bolt for specific road surface, i.e. concrete

Bolts are supplied in pairs

JUMBO™ RAMP ASPHALT BOLT FIXING DIMENSIONS

Bolt Size: M12 x 100mm

LIMITATIONS OF USE

Temporary Speed Restrictors are not for use on Public Roads

Damage to vehicle components is possible if the speed bumps are approached at speeds higher than recommended

JUMBO™ RAMP ASPHALT BOLT FIXING CONFORMITY

Temporary Speed Restrictors do not meet any British or European Standards and are not covered by the Road Traffic Act